

Premium motors
LSES - Aluminium frame
FLSES - Cast iron frame
IP55 - 3-phase - 400V - 50Hz



Type	2-pole 3000 min ⁻¹					
	Rated power P_N kW	Rated speed N_N min ⁻¹	Rated torque M_N N.m	Rated current $I_N(400V)$ A	Power factor $\cos \varphi$ 4/4	Efficiency IEC 60034-2-1 2007 η 4/4
LSES 80 L	0.75	2892	2.5	1.4	0.84	80.7
LSES 80 LU	1.1	2894	3.6	2.2	0.83	82.7
LSES 90 SL	1.5	2870	5	3	0.85	84.2
LSES 90 LU	2.2	2885	7.3	4.9	0.90	85.9
LSES 100 LG	3	2931	9.8	5.7	0.89	87.1
LSES 112 MU	4	2935	13	7.4	0.89	88.1
LSES 132 SU	5.5	2925	18	10	0.91	89.2
LSES 132 SM	7.5	2940	24.4	14.2	0.86	90.1
LSES 132 M	9	2940	29.2	17	0.84	90.7
LSES 160 MP	11	2940	35.7	19	0.90	91.2
LSES 160 M	15	2952	48.5	26.6	0.89	91.9
LSES 160 L	18.5	2950	59.9	32.5	0.88	92.5
LSES 180 MUR	22	2965	70.9	38.8	0.91	92.7
LSES 200 LR	30	2954	97.0	51.5	0.92	93.3
LSES 200 L	37	2950	120	63.3	0.90	93.7
LSES 225 MT	45	2955	145	80	0.86	94
LSES 250 MZ	55	2955	178	94.6	0.88	94.3
LSES 280 SC	75	2975	241	130	0.89	94.8
LSES 280 MC	90	2970	289	148	0.90	95
LSES 315 SN	110	2972	353	187	0.92	95.2
LSES 315 MP	132	2981	423	221	0.91	95.4
LSES 315 MR	160	2981	513	276	0.89	95.6
LSES 315 MR	200	2983	640	352	0.86	95.8
FLSES 315 LB	200	2978	643	335	0.90	95.8
FLSES 355 LA	250	2978	802	428	0.88	95.9
FLSES 355 LB	315	2981	1009	536	0.88	96.4
FLSES 355 LC	355	2982	1137	617	0.86	96.5

Type	4-pole 1500 min ⁻¹					
	Rated power P_N kW	Rated speed N_N min ⁻¹	Rated torque M_N N.m	Rated current $I_N(400V)$ A	Power factor $\cos \varphi$ 4/4	Efficiency IEC 60034-2-1 2007 η 4/4
LSES 80 LG	0.75	1435	5	1.6	0.81	82.5
LSES 90 SL	1.1	1447	7.3	2.2	0.81	84.1
LSES 90 LU	1.5	1450	9.9	3.2	0.80	85.3
LSES 100 LR	2.2	1450	14.5	4.5	0.81	86.7
LSES 100 LG	3	1460	19.6	6.1	0.81	87.8
LSES 132 SU	4	1467	26	8	0.82	88.6
LSES 132 SM	5.5	1463	35.9	10.9	0.82	89.6
LSES 132 MU	7.5	1465	48.9	14.5	0.82	90.4
LSES 160 MR	9	1465	58.7	17.1	0.84	91.0
LSES 160 M	11	1464	71.8	20.6	0.84	91.4
LSES 160 LUR	15	1468	97.6	28	0.83	92.1
LSES 180 M	18.5	1471	120	35.1	0.82	92.6
LSES 180 LUR	22	1471	143	41	0.83	93.0
LSES 200 L	30	1475	194	55.8	0.83	93.6
LSES 225 SG	37	1480	239	68.4	0.81	93.9
LSES 225 MG	45	1485	289	84.6	0.81	94.2
LSES 250 ME	55	1483	354	100	0.83	94.6
LSES 280 SD	75	1485	482	137	0.83	95.0
LSES 280 MD	90	1488	578	163	0.84	95.2
LSES 315 SP	110	1487	706	199	0.84	95.4
LSES 315 MP	132	1484	849	243	0.83	95.6
LSES 315 MP	160	1483	1030	290	0.84	95.8
LSES 315 MR	200	1482	1289	352	0.86	96.0
FLSES 315 LB	200	1484	1287	349	0.86	96.1
FLSES 355 LA	250	1489	1603	437	0.86	96.0
FLSES 355 LB	315	1488	2022	544	0.87	96.1
FLSES 355 LC	355	1487	2220	626	0.85	96.3

Other finishes, number of poles and power ratings available on request.



Nema Premium motors LSES - Aluminium frame

IP55 - 3-phase - 460V - 60Hz

NEMA
Premium®



LEROY
SOMER

2-pole
3600 min⁻¹

Type	Rated power P_N HP	Rated speed N_N min ⁻¹	Rated torque M_N N.m	Rated current $I_N(400V)$ A	Power factor $\cos \varphi$ 4/4	Efficiency IEEE 112B η 4/4
LSES 80 L	1	3475	2.1	1.4	0.84	80.2
LSES 80 LU	1.5	3480	3.1	2	0.85	84
LSES 90 SL	2	3500	4.1	2.7	0.82	85.5
LSES 90 LU	3	3550	6.0	4	0.8	86.5
LSES 112 MG	5	3540	10.1	5.9	0.89	88.5
LSES 132 S	7.5	3580	14.9	9.2	0.84	90.2
LSES 132 M	10	3545	20.1	11.9	0.87	90.4
LSES 160 MP	15	3550	30.1	17.7	0.87	91.1
LSES 160 MR	20	3540	40.3	23.4	0.87	91.7
LSES 160 L	25	3560	50.1	29	0.88	91.7
LSES 180 MT	30	3550	60.2	34	0.89	92.8
LSES 200 LR	40	3560	80.1	43.9	0.92	92.6
LSES 200 L	50	3565	100	56.5	0.89	93
LSES 225 MT	60	3565	120	68.9	0.87	93.6
LSES 250 MZ	75	3560	150	84.1	0.89	93.8
LSES 280 SC	100	3570	200	110	0.9	94.3
LSES 280 MD	125	3570	250	137	0.9	95
LSES 315 SN	150	3575	299	163	0.9	95.4
LSES 315 MR	200	3580	398	218	0.9	95.4

4-pole
1800 min⁻¹

Type	Rated power P_N HP	Rated speed N_N min ⁻¹	Rated torque M_N N.m	Rated current $I_N(400V)$ A	Power factor $\cos \varphi$ 4/4	Efficiency IEEE 112B η 4/4
LSES 80 LG	1	1755	4.1	1.4	0.79	85.5
LSES 90 SL	1.5	1755	6.1	2	0.8	86.5
LSES 90 LU	2	1765	8.1	2.8	0.77	86.6
LSES 100 LU	3	1750	12.2	3.9	0.8	89.5
LSES 112 MU	5	1765	20.2	6.6	0.79	89.5
LSES 132 MU	7.5	1770	30.2	9.1	0.84	91.7
LSES 160 LR	10	1770	40.3	12.4	0.82	91.9
LSES 160 M	15	1775	60.2	18.8	0.8	93.2
LSES 160 LUR	20	1765	80.8	25.5	0.79	93
LSES 180 MUR	25	1780	100	31.3	0.8	93.6
LSES 180 LUR	30	1770	121	35.7	0.84	93.6
LSES 200 L	40	1780	160	49.1	0.81	94.1
LSES 225 SR	50	1780	200	61.8	0.8	94.6
LSES 225 MG	60	1785	240	72.1	0.82	95
LSES 250 ME	75	1785	300	89.7	0.82	95.4
LSES 280 SD	100	1785	399	120	0.82	95.4
LSES 280 MD	125	1785	499	151	0.81	95.4
LSES 315 SP	150	1790	597	180	0.82	95.8
LSES 315 MR	200	1790	796	229	0.85	96.2

Other finishes, number of poles and power ratings available on request.



1 to 500 HP



1 to 500 HP



Need more information?

- Dimensions
- 2D and 3D CAD files

Use our unique solution - the Leroy-Somer Configurator

