



## Type 2536 Rotor-X Standard Mount Paddlewheel

### Flow:

- Operating range: 0.1 to 6 m/s, 0.3 to 20 ft/s
- Open collector output
- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Max Pressure rating: PP 12.5 bar @ 20 °C, 180 psi @ 68 °F PVDF 14 bar @ 20 °C, 200 psi @ 68 °F
- Rotor: PVDF
- Compatibility: 8900, 9900, 9900-1BC, 9950
- Power source: <20mA @ 3.3 to 24 VDC
- \*Only Signet installation fittings

MFR #	Body	Pin	Pipe Size (inch)	Sensor Type	Code
3-2536-P0	PP	Titanium	0.5 - 4.0	-X0	<b>198 840 143</b>
3-2536-P1	PP	Titanium	5.0 - 8.0	-X1	<b>198 840 144</b>
3-2536-P2	PP	Titanium	10.0 - 36.0	-X2	<b>198 840 145</b>
3-2536-T0	PVDF	PVDF	0.5 - 4.0	-X0	<b>198 840 149</b>
3-2536-V0	PVDF	Hastelloy C	0.5 - 4.0	-X0	<b>198 840 146</b>
3-2536-V1	PVDF	Hastelloy C	5.0 - 8.0	-X1	<b>198 840 147</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.