



Applications

- Strainers must be used wherever it is essential that the fluid flowing through pipe lines be maintained free of foering solid matter, to assure the correct operation of the solenoid valve.
- Suitable Medium: water, oil, air and some corrosive liquids.

CONEXION ØA	B	C	D
1/2" BSP	60	46	13
3/4" BSP	75	55	15
1" BSP	85	60	20
1 1/2" BSP	110	76	25
2" BSP	130	100	35

mesurements: mm

CONEXION ØA	B	C	D
1/2" BSP	2.36	1.81	0.5
3/4" BSP	2.95	2.16	0.6
1" BSP	3.34	2.36	0.75
1 1/2" BSP	4.33	3	1
2" BSP	5.11	4	1.37

measurements: in

Main Characteristic

- AISI 316 (CF8M) Body.
- AISI 316 Mesh. 100 microns.
- PTFE - Seal.
- Cover with drainage connection.

Optional

- NPT connections

Technical Specifications

ø Pipe ins.	Flow factor		Δp Maximum		Weight		Maximum temp.		Catalog Nº.
	Kv	Cv	bar	psi	kg	Lb	°C	°F	
1/2	6	7	16	240	0.17	0.37	232	458	3059II04
3/4	12	14			0.25	0.55			3059II06
1	19	22			0.5	1.1			3059II08
1.1/2	40	47			0.9	1.98			3059II12
2	65	76			1.4	3.0			3059II16