



Type 515 Rotor-X Standard Mount Paddlewheel

Flow:

- Operating range: 0.3 to 6 m/s, 1 to 20 ft/s
- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Max Pressure rating: PP 12.5 bar @ 20 °C, 180 psi @ 68 °F PVDF 14 bar @ 20 °C, 200 psi @ 68 °F
- Power source: Self powered
- Rotor: PVDF
- Compatibility: 8150, 8900, 9900, 9900-1BC, 9950
- *Only Signet installation fittings
- Standard: FKM O-rings (EPDM or FFKM on request)
- Other materials of rotor and axis on request

MFR #	Body	Pin	Pipe Size (inch)	Sensor Type	Code
P51530-H0	PP	Hastelloy C	0.5 - 4.0	-X0	198 801 659
P51530-P0	PP	Titanium	0.5 - 4.0	-X0	198 801 620
P51530-P1	PP	Titanium	5.0 - 8.0	-X1	198 801 621
P51530-P2	PP	Titanium	10.0 - 36.0	-X2	198 801 622
P51530-S0	PP	PVDF	0.5 - 4.0	-X0	198 801 661
P51530-T0	PVDF	PVDF	0.5 - 4.0	-X0	198 801 663
P51530-T1	PVDF	PVDF	5.0 - 8.0	-X1	198 801 664
P51530-V0	PVDF	Hastelloy C	0.5 - 4.0	-X0	198 801 623
P51530-V1	PVDF	Hastelloy C	5.0 - 8.0	-X1	198 801 624
P51530-V2	PVDF	Hastelloy C	10.0 - 36.0	-X2	198 801 625

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.