

**NEW**

# Elcometer 456

IPC Dry Film Thickness Gauge

elcometer®  
inspection equipment

**Pre-calibrated with 4 surface profiles to measure dry film thickness on shot or grit blasted substrates**

● **No calibration required - just select the relevant surface profile and start measuring**

● **Easy to use straight from the box - minimum training required**

● **Fully portable, rugged hand-held design ideal for use in the field**

- Pre-calibrated with 4 profile ranges
- Displays 3 individual readings together with the average
- Built in integral probe measures in mils or microns
- Measures on flat or curved surfaces
- Bluetooth® to PC, iOS & Android™ devices



Made for



iPod



iPhone



iPad

**Android™**



## Elcometer 456

## IPC Dry Film Thickness Gauge

The Elcometer 456 Industrial Protective Coating Thickness Gauge\* is pre-calibrated to measure DFT on shot or grit blasted steel substrates.

### STANDARDS:

ASTM D7091, ISO 2808, ISO 19840,  
SSPC PA-2, US Navy NSI 009-32

new

Pre-calibrated with 4 profile ranges:

Profile	Metric	Imperial
Smooth	0-25µm	0-1mil
Fine	25-60µm	1-2mils
Medium	60-100µm	2-3mils
Coarse	>100µm	3-4mils

Displays 3 individual readings together with their average in microns or mils

Built in integral probe for stable, repeatable readings on flat or curved surfaces



Easy to use multi-lingual menu structure

Stores up to 150,000 readings in alphanumeric batches

USB or Bluetooth® data output to the ElcoMaster® App or your own software application



\* USA patent number US6243 661



Made for  
iPod iPhone iPad

Android™

available with  
Bluetooth®  
wireless technology

compatible with  
ElcoMaster®

Elcometer 456 IPC: Made for iPhone 6 Plus, iPhone 6, iPhone 5s, iPhone 5c, iPhone 5, iPhone 4s, iPhone 4, iPad Air 2, iPad mini 3, iPad Air, iPad mini 2, iPad (3rd and 4th generation), iPad mini, iPad 2, and iPod touch (4th and 5th generation). "Made for iPod," "Made for iPhone," and "Made for iPad" mean that an electronic accessory has been designed to connect specifically to iPod, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPod, iPhone, or iPad may affect wireless performance.

## IPC Dry Film Thickness Gauge

Elcometer 456

### Product Features

Model	Model S	Model T
Part Number	A456CFI1-IPC	A456CFTI1-IPC
Test Certificate	●	●
Fast, accurate reading rate; 70+ readings per minute	■	■
Data output	■	■
USB; to computer	■	■
Bluetooth®; to computer, Android™ & iOS¹ devices	■	■
On screen statistics; in Batch Mode		■
Number of readings; $\eta$ , Mean (average); $\bar{x}$ , Standard deviation; $\sigma$ , Highest reading; Hi, Lowest reading; Lo, Coefficient of variation; CV%, Elcometer index value²; EIV, Nominal dry film thickness; NDFT, High & low limits; definable audible & visual alarms, Number of readings above high limit; Number of readings below low limit		■
ElcoMaster® software & USB cable		■
Integral Probe type; Ferrous (F)	■	■
Measurement range; 0 - 1,500 $\mu$ m (0 - 60mils)	■	■
Resolution; 10 $\mu$ m/1mil (where 5 $\mu$ m/0.5mil is rounded up)	■	■
Accuracy³; $\pm 5\%$	■	■
Minimum substrate thickness; 300 $\mu$ m (12mils)	■	■
Pre-calibrated with 4 profile ranges;	■	■
Smooth 0-25 $\mu$ m 0-1mil, Fine 25-60 $\mu$ m 1-2mils, Medium 60-100 $\mu$ m 2-3mils, Coarse >100 $\mu$ m 3-4mils	■	■
Auto calibration	■	■
Calibration memory type; gauge (g) or gauge & batch (gb)	g	gb
Number of batches; with unique calibrations		2,500
Calibration lock; with optional PIN code unlock	■	■
Delete last reading	■	■
Gauge memory; number of readings		150,000
Individual batch calibrations; sent to PC via ElcoMaster® software		■
Limits; user definable audible & visual pass/fail warnings		■
Gauge & batch specific limits		■
Date and time stamp		■
Review, clear & delete batches		■
Batch types; normal, counted average		■
Batch review graph		■
Copy batches and calibration settings		■
Alpha-numeric batch names; user definable on the gauge		■

### Technical Specification

Battery Type	2 x AA batteries, rechargeable batteries can also be used
Battery Life⁴	Alkaline: Approx. 16 hours Lithium: Approx. 24 hours
Gauge Dimensions (h x w x d)	141 x 73 x 37mm (5.55 x 2.87 x 1.46")
Weight (including batteries)	156g (5.5oz)
Operating Temperature	-10 to 50°C (14 to 122°F)
Packing List	Elcometer 456 IPC Gauge, calibration foils, wrist harness, protective case, 1 x screen protector, USB cable, test certificate, 2 x AA batteries & user guide.

¹ Visit [www.elcometer.com/sdk](http://www.elcometer.com/sdk) to find out how to integrate Elcometer's MFi certified products to your App.

● Test certificate supplied as standard.

² Elcometer Index Values are used in the automotive industry to assess a coating's overall quality; USA patent number US7606671B2    ³ When in test calibration mode

⁴ Using default settings & lithium batteries, alkaline or rechargeable batteries may differ





**elcometer®**  
www.elcometer.com

elcometer.be • elcometer.fr • elcometer.de  
elcometer.nl • elcometer.jp • elcometer.com.sg

#### ENGLAND

Elcometer Limited  
Manchester M43 6BU  
Tel: +44 (0)161 371 6000  
Fax: +44 (0)161 371 6010  
sales@elcometer.com  
www.elcometer.com

#### BELGIUM

Elcometer SA  
Tel: +32 (0)4 379 96 10  
Fax: +32 (0)4 374 06 03  
be\_info@elcometer.com  
www.elcometer.be

#### FRANCE

Elcometer Sarl  
Tel: +33 (0)2 38 86 33 44  
Fax: +33 (0)2 38 91 37 66  
fr\_info@elcometer.com  
www.elcometer.fr

#### GERMANY

Elcometer Instruments GmbH  
Tel: +49(0)7361 52806 0  
Fax: +49(0)7361 52806 77  
de\_info@elcometer.com  
www.elcometer.de

#### THE NETHERLANDS

Elcometer B.V.  
Tel: +31 (0)30 259 1818  
Fax: +31 (0)30 210 6666  
nl\_info@elcometer.com  
www.elcometer.nl

#### JAPAN

Elcometer KK  
Tel: +81-(0)3-6869-0770  
Fax: +81-(0)3-6433-1220  
jp\_info@elcometer.com  
www.elcometer.jp

#### REPUBLIC OF SINGAPORE

Elcometer (Asia) Pte Ltd  
Tel: +65 6462 2822  
Fax: +65 6462 2860  
asia@elcometer.com  
www.elcometer.com.sg

#### UNITED ARAB EMIRATES

EL Inspection & Blasting  
Equipment LLC  
Tel: +971 4 295 0191  
Fax: +971 4 295 0192  
uae\_sales@elcometer.com  
www.elcometer.ae

#### USA

##### MICHIGAN

Elcometer Inc  
Tel: +1 248 650 0500  
Toll Free: 800 521 0635  
Fax: +1 248 650 0501  
inc@elcometer.com  
www.elcometer.com

##### TEXAS

Elcometer of Houston  
Tel: +1 713 450 0631  
Toll Free: 800 521 0635  
Fax: +1 713 450 0632  
inc@elcometer.com  
www.elcometer.com

Elcometer 456 IPC: Made for iPhone 6 Plus, iPhone 6, iPhone 5s, iPhone 5c, iPhone 5, iPhone 4s, iPhone 4, iPad Air 2, iPad mini 3, iPad Air, iPad mini 2, iPad (3rd and 4th generation), iPad mini, iPad 2, and iPod touch (4th and 5th generation).

"Made for iPod," "Made for iPhone," and "Made for iPad" mean that an electronic accessory has been designed to connect specifically to iPod, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPod, iPhone, or iPad may affect wireless performance.

iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a trademark of Apple Inc., registered in the U.S. and other countries. Suitable for mobile devices running Android software version 2.1 and upwards. Android™ and Google Play are trademarks of Google Inc. Elcometer and ElcoMaster are registered trademarks of Elcometer Limited. All other trademarks acknowledged.

Due to our policy of continuous improvement, Elcometer Limited reserves the right to change specifications without notice.

© Elcometer Limited, 2017. All rights reserved. No part of this document may be reproduced, transmitted, stored (in a retrieval system or otherwise), or translated into any language, in any form, or by any means, without the prior written permission of Elcometer Limited.